



# ISP-2 Installation Machine

**N**ow there is a fast, easy and accurate way to install O-rings into parts and assemblies. The ISP-2 Installation Machine can position O-rings and seals up to 2.25" O.D. into a desired part. The O-rings or seals are fed by a vibratory feeder bowl into a track where they are positioned onto an installation mandrel. The operator then lightly pushes the part into the mandrel and the O-ring or seal is automatically installed at the specified location.

- Benchtop Machine
- Installation Rate up to 30 Cycles/ Minute (1,800 per hour)
- Digital Counter
- Right-hand or Left-hand Configuration
- Easy Tooling Change-Over (Less than 10 minutes)
- PLC can Easily be Expanded for Automated System
- Installs



- O-Rings      - Quad Rings      - Teflon® Seals      - Crimp Seal

## Standard ISP-2 Dimensions

Width 26.88" ( 682.75 mm) x Depth 28.56" (725.42 mm) x Height 18.50" (469.90 mm)

\* Foot pedal required for machines not incorporated into automated system.

## Machine Specifications

115 VAC, 60 Hz. (Other voltages available on request.)

90 psi (6.205 bar) air supply.

## Ring or Seal Specifications

1.01"- 2.25" O.D. (25.65 mm - 57.15 mm)

\*Application Limitations will vary depending on O-ring or seal O.D., cross section and material composition.

**NOTE:** For applications with O-rings or seals 1" or smaller, see our ISP-1 machine.

## ISP-2 Options

**Low Lube Reservoir Sensor** - Shuts down the machine when lubricant reservoir needs refilling.

**Work Stand** - Steel constructed stand provides sturdy base for machine operation.

**Stainless Steel Parts** - Available for "clean room" applications.



*For more information or a quote contact:*

# Automated Industrial Systems Inc.

4238 W. 12th Street • Erie, PA 16505

Phone: (814) 838-2270 • Fax: (814) 833-5661 • E-mail: [info@asporing.com](mailto:info@asporing.com) • <http://www.asporing.com>